



MIX-SF FRONTAL MIXING BUCKET SAFE DISCHARGE





- PATENTED
- HB400



NB: AT THE TIME OF ORDER, PLEASE NOTIFY THE VOLTAGE OF THE ELECTRICAL SYSTEM (12-24 V)

GEARBOX TRANSMISSION DELIVERS HIGH PERFORMANCE AND DOES NOT REQUIRE CONTINUOUS MAINTENANCE INTERVENTIONS. THE USE OF DUAL CROSS RELIEF AND FLOW DIVIDER VALVES GRANTS EFFECTIVENESS AND RELIABILITY EVEN IN THE MOST DIFFICULT WORK CONDITIONS. THE SKID LOADER HITCH IS SUPPLIED AS STANDARD (EXCEPT FOR MODELS MIX 800SF-1000SF-1200SF).



MOD.	MIX 150SF.2	MIX 200SF.2	MIX 250SF.2	MIX 350SF.2	MIX 450SF.2	MIX 600SF.2	MIX 800SF.2	MIX 1000SF.2	MIX 1200SF.2	
A MIN (MM)	1000 (39)	1100 (43)	1350 (53)	1350 (53)	1670 (66)	1750 (69)	1830 (72)	2000 (79)	2000 (79)	
B MIN (MM)	1265 (49,8)	1360 (53,5)	1610 (63,3)	1630 (64)	1946 (77)	2018 (79)	2230 (87,7)	2440 (96)	2440 (96)	
C MIN (MM)	620 (24)	650 (26)	650 (26)	720 (28)	720 (28)	835 (33)	910 (36)	990 (39)	1100 (43)	
D MIN (MM)	530 (21)	580 (23)	610 (24)	680 (27)	680 (27)	800 (31)	840 (33)	910 (36)	980 (39)	
W/O COUPLER	KG (KG)	260 (573)	315 (694)	350 (771)	370 (816)	425 (937)	555 (1223)	675 (1488)	850 (1874)	905 (1995)
W/O COUPLER	KG (KG)	600 (1323)	775 (1708)	925 (2039)	1175 (2590)	1460 (3219)	1930 (4254)	2515 (5545)	3150 (6944)	3665 (8080)
L (GAL)	150 (39,6)	200 (52,8)	250 (66)	350 (92,5)	450 (118,9)	600 (158,5)	800 (211,3)	1000 (264,2)	1200 (317)	
DISCHARGE PIPE	MIN (MM)	210 (8)	210 (8)	210 (8)	210 (8)	210 (8)	210 (8)	210 (8)	210 (8)	
MAX	L/MIN (GAL/MIN)	70 (19)	70 (19)	70 (19)	70 (19)	70 (19)	70 (19)	70 (19)	100 (26)	
MAX	BARS (PSI)	200 (2901)	200 (2901)	200 (2901)	200 (2901)	200 (2901)	200 (2901)	200 (2901)	200 (2901)	
CONNECT		STD 14 PIN	STD 14 PIN	STD 14 PIN	STD 14 PIN	STD 14 PIN	STD 14 PIN	STD ELECTRIC KIT	STD ELECTRIC KIT	STD ELECTRIC KIT
COUPLER		AT. SKID	AT. SKID	AT. SKID	AT. SKID	AT. SKID	AT. SKID	W/O COUPLER	W/O COUPLER	W/O COUPLER

STANDARD TECHNICAL FEATURES

- SAFE LOCKING/DISCHARGE (PATENTED)**
THE OPERATOR LOCKS THE DISCHARGE PIPE FROM THE BUCKET'S SIDE IN THE SAFEST WORK CONDITION.
- CONTROL ROD FOR THE DISCHARGE PIPE**
IT ENABLES THE PIPE'S DISPLACEMENT FOR THE SIDE POURING.
- AUGER REMOVAL**
THE BUCKET'S BODY HAS BEEN DESIGNED IN A SUCH WAY THAT THE ENTIRE AUGER CAN BE REMOVED THUS MAKING THE MAINTENANCE OPERATION EASIER.
- GEARMOTOR**
IT GUARANTEES HIGH PERFORMANCES TO THE ENTIRE SYSTEM.
- ELECTRIC KIT (FROM MIX 800SF TO MIX 1200SF)**
ENABLES SELECTION OF MIXING OR UNLOADING HATCH FROM THE CAB.
- 14 PIN HD36-18-14SE CONNECT (FROM MIX 150SF TO MIX 600SF)**
THE 14-PIN PLUG IS SUPPLIED DISASSEMBLED, IF NO INFORMATION ON THE PLUG WIRING IS PROVIDED, PLEASE CHECK THAT THE MAIN MACHINE IS EQUIPPED WITH A 14-PIN MULTIPOLE SOCKET (STANDARD CANGINI CONFIGURATION). ON THE CONTRARY, THE OPTIONAL N.9 ELECTRICAL KIT IS REQUIRED.

NB: THE EQUIPMENT IS SUPPLIED COMPLETE WITH PIPES AND CONNECTIONS

OPTIONAL

- ARTICULATED LOADERS, BACKHOE LOADERS AND TELEHANDLER HANDLERS HITCH**
IT'S POSSIBLE TO ADD THE HITCH FOR ARTICULATED LOADERS, BACKHOE LOADERS AND TELEHANDLER TO THE SKID LOADER HITCH (STANDARD EXCEPT FOR MODELS MIX 800SF-1000SF-1200SF).
- SHOVEL ATTACHMENT**
FOR 800SF-1000SF-1200SF MODELS ONLY
- FLOWRATE REDUCERS**
COMPULSORY FOR MACHINES WITH OILFLOW EXCEEDING THE REQUIRED ONE
- 8 PIN HD36-18-8SE CONNECT / ELECTRIC KIT (FROM MIX 150SF TO MIX 600SF)**

